

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 98/07805

(51) International Patent Classification 6 :

C10G

A2

(11) International Publication Number:

(43) International Publication Date: 26 February 1998 (26.02.98)

(21) International Application Number: PCT/US97/14761

(22) International Filing Date: 22 August 1997 (22.08.97)

(30) Priority Data: 60/024,306 23 August 1996 (23.08.96) US

(71) Applicant (for all designated States except US): EXXON
CHEMICAL PATENTS INC. [US/US]; 5200 Bayway
Drive, Baytown, TX 77520-5200 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): IACCINO, Larry L. [-/US];
2017 San Joaquin Parkway, Friendswood, TX 77546 (US).

(74) Agents: RUSSELL, Linda, K.; Exxon Chemical Company, P.O.
Box 2149, Baytown, TX 77522-2149 (US) et al.

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,
GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ,
PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT,
UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS,
MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY,
KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH,
DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,
SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML,
MR, NE, SN, TD, TG).

Published

Without international search report and to be republished
upon receipt of that report.

(54) Title: HETEROATOM REMOVAL THROUGH COUNTERCURRENT SORPTION

(57) Abstract

The present invention relates to a process for heteroatom removal, particularly during process excursions, from petroleum and chemical hydrocarbon streams. The invention is comprised of at least two zones through which the hydrocarbon stream and a hydrogen-containing treat gas flow. The first zone contains a bed of heteroatom hydroprocessing catalyst in contact with hydrogen-containing treat gas and the second zone contains heteroatom sorbent material(s) through which the hydrocarbon stream flows countercurrent to the up flowing hydrogen-containing treat gas.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

HETEROATOM REMOVAL THROUGH COUNTERCURRENT SORPTION

This application claims priority to U.S. Provisional Patent Application No.
5 60/024,306, filed August 23, 1996.

Field of the Invention

The present invention relates to a process for heteroatom removal from a
10 petroleum and/or chemical stream. The present invention is particularly
useful in the process of ensuring the desired product quality by enabling the
heteroatom removal process to continue in the event of a process excursion.

Background of the Invention

15 Heteroatom removal is one of the fundamental processes of the refining and
petrochemical industries. Heteroatoms are defined to be those atoms other
than hydrogen and carbon, present in hydrocarbon streams, including but not
limited to, sulfur, nitrogen, oxygen, and halogens. These atoms are typically
20 found as organo heteroatom molecules wherein the heteroatoms molecules
make-up part of the carbon hydrogen backbone. Unless otherwise specified,
the expression "heteroatom" is hereafter meant to encompass the elemental
form of the heteroatom itself as well as its combined counterpart species as
an organic and as combined with hydrogen (i.e. organo heteroatom and
25 hetero-hydride, respectively).

The removal of such heteroatoms by conversion to the corresponding hetero-
hydride (i.e. hydrogen sulfide, ammonia, water, or hydrogen halide) is
typically achieved in industry by reaction of the hydrocarbon stream
30 containing the heteroatoms with hydrogen over a suitable hydroprocessing
catalyst which is designed to meet the required product quality specifications,

or to supply a low or a substantially reduced level (hereafter low is meant to also include essentially no heteroatoms) heteroatom stream to subsequent heteroatom sensitive processes, catalysts, or product dispositions.

- 5 Typically, catalytic heteroatom removal of a stream is carried out in co-current reactors in which both the preheated feed stream and a hydrogen-containing treat gas are introduced to one or more beds of heteroatom removal catalyst. The liquid feed stock, any vaporized hydrocarbons, and hydrogen-containing treat gas all flow together through the catalyst bed(s). The resulting
10 combined vapor phase and liquid phase effluents are normally separated in a series of one or more separator vessels, or drums, downstream of the reactor.

- Conventional co-current catalytic heteroatom removal has met with a great
15 deal of commercial success; however, it has limitations. For example, because of hydrogen consumption and treat gas dilution by light reaction products, hydrogen partial pressure decreases between the reactor inlet and outlet. At the same time, any heteroatom hydroprocessing reactions that take place results in increased concentrations of hetero-hydride which strongly
20 inhibits the catalytic activity and performance of most hydroprocessing catalysts through competitive adsorption onto the catalyst. Thus, the downstream portions of catalyst in co-current reactors are often limited in reactivity because of the simultaneous occurrence of multiple negative effects, such as the low H₂ partial pressure and the presence of the high
25 concentrations of hetero-hydride.

- Process excursions can occur during operation of a co-current reactor. Process excursions include events such as variation in quality or rate of the liquid feed stream or hydrogen containing treat gas stream, start-up and shut-
30 down of the unit, emergency depressuring of the reactor to avert hazardous conditions, or other process upsets commonly experienced by commercial

operating units. During such process excursions, there is a high probability that the heteroatom removal capability of the co-current reactor will be diminished and either the heteroatoms in their original form as organo heteroatom molecules or as the hetero-hydride will come in contact with the heteroatom sensitive downstream process or catalyst. Such contact may cause temporary or permanent impairment of the sensitive process or catalyst and result in unacceptable final product quality which may require significant time and expense (i.e., replacement of a poisoned catalyst) to rectify.

A bed of heteroatom sorbent can be used to protect downstream processes or catalyst but, if a bed of heteroatom sorbent is used downstream of a co-current heteroatom removal zone in co-current operation, a separation step for removal of the hetero-hydride is required. The sorbents bed's capacity can be quickly diminished if substantial heteroatom breakthrough of the upstream heteroatom hydroprocessing catalyst occurs and restoration of capacity will typically require off stream regeneration.

It is relatively well known that heteroatom removal can be accomplished more efficiently in a countercurrent flow hydroprocessing system wherein a hydroprocessing catalyst system through which the liquid hydrocarbon feedstream flows downward and the hydrogen containing treat gas is passed upward. The counter current flow system has the potential to produce significantly lower heteroatom content streams and to do so more efficiently.

While significant potential advantage exist for the application of counter current hydroprocessing; especially when coupled with the use of very high activity heteroatom sensitive catalysts, it is presently of very limited commercial use. US-A-3,147,210 discloses a two stage process for the hydrofining-hydrogenation of high-boiling range aromatic hydrocarbons. The feed stock is first subjected to catalytic hydrofining, preferably in co-current

flow with hydrogen, then subjected to hydrogenation over a heteroatom sensitive noble metal hydrogenation catalyst countercurrent to the flow of a hydrogen containing treat gas. US-A-3,767,562 and US-A-3,775,291 disclose a countercurrent process for producing jet fuels, whereas the jet fuel is first hydrodesulfurized in a co-current mode prior to two stage countercurrent hydrogenation. US-A-5,183,556 also discloses a two stage co-current/countercurrent process for hydrofining and hydrogenating aromatics in a diesel fuel stream.

One reason that countercurrent flow hydroprocessing has not been more widely commercialized is that these type of reactors are more prone to deterioration in performance due to operating excursions than conventional co-current reactor systems. Process excursions include events such as variation in quality or rate of the liquid feed stream or hydrogen containing treat gas stream, start-up and shut-down of the unit, emergency depressuring of the reactor to avert hazardous conditions, or other process upsets commonly experienced by commercial operating units. During said process excursions, there is a high probability that the heteroatom removal capability of the countercurrent reactor will be diminished and either the heteroatoms in their original form as organo heteroatom molecules or as the hetero-hydride will come in contact with the heteroatom sensitive downstream process or catalyst. Said contact may cause temporary or permanent impairment of the sensitive process or catalyst and result in unacceptable final product quality which may require significant time and expense (i.e., replacement of a poisoned catalyst) to rectify.

In light of the above, there is still a need for an improved cocurrent or countercurrent heteroatom removal process, that can reliably operate under commercial plant conditions, to produce streams containing low heteroatom content.

Summary of the Invention

In accordance with the present invention, there is provided a process for the
5 heteroatom removal from a hydrocarbon stream comprising:

- 10 (a) feeding said feedstock stream to a first reaction zone comprising a bed of heteroatom hydroprocessing catalyst in contact with a hydrogen-containing treat gas wherein said first reaction zone is operating at conditions effective to remove a first portion of the hetero-atom content of said feedstock stream, wherein said first portion removed from said feedstock stream is in the range of 20% to 100%;
- 15 (b) passing the liquid product stream from (a) to a sorbent zone comprising a bed of heteroatom sorbent material in contact with a hydrogen-containing treat gas wherein said liquid product stream from (a) and said hydrogen-containing treat gas are flowing in a countercurrent direction, wherein said sorbent zone is operating under conditions effective to remove a second portion of the hetero-atom from said liquid product stream from
20 (a), wherein said second portion removed from said feedstock stream is in the range of 0% to 80%; and
- 25 (c) recovering a liquid product stream from (b) wherein the amount of heteroatom remaining is in the range of from 0% to 20%, basis the starting hydrocarbon feedstream which has not be subjected to a heteroatom removal process.

Detailed Description of the Invention

While the heteroatom removal process of the present invention is applicable
5 to all heteroatom bearing compounds common to petroleum and chemical
streams, the process is particularly suitable for the removal of the least
reactive, most highly refractory heteroatom species. The process of the
present invention can result in a product stream which contains essentially no
heteroatoms. For purposes of this invention, the phrase "essentially no
10 heteroatoms", depends upon the overall process being considered, but can
be defined as a value substantially less than about 100 wppm, preferably less
than about 10 wppm, more preferably less than about 1 wppm, and most
preferably less than about 0.1 wppm as measured by existing, conventional
analytical technology. The invention is also applicable to consistent
15 production of low heteroatom content streams. That is to say that in cases
where steady state operation of the upstream heteroatom removal catalyst
results in a steady state heteroatom concentration of X ppm; the sorbent will
equilibrate with the concentration of X ppm, but when a process excursion
occurs and the heteroatom concentration significantly exceeds X ppm then
20 the sorbent will adsorb or absorb more heteroatom and prevent adverse
effects on downstream catalysts or processes.

The feed stocks of the present invention are subjected to heteroatom removal
in at least one catalyst bed, or reaction zone, wherein feed stock flows co-
25 current or countercurrent to the flow of a hydrogen-containing treat gas.
Each zone may be immediately preceded and followed by a non-reaction
zone where products may be removed and/or feed or treat gas introduced.
The non-reaction zone will be a zone which is typically empty and does not
contain a catalyst that is capable of removing any heteroatoms, but it could
30 contain a drying agent, such as a molecular sieve bed. In a preferred

embodiment, such a non-reaction zone is an empty cross-section in the reaction vessel.

The liquid effluent from the reaction zone(s), is passed on to at least one
5 sorbent zone containing one or more heteroatom sorbents in contact with a
countercurrent flow of hydrogen containing treat gas. The liquid effluent, now
with reduced low heteroatom content, wherein the initial level of heteroatom
in the hydrocarbon feedstream is reduced by levels in the range of from about
20% to about 100%, may be sent to a heteroatom sensitive process, catalyst,
10 or product disposition. In a preferred embodiment, the liquid effluent contains
a heteroatom content which has been reduced by levels in the range from
about 50% to about 100%, more preferably from about 75% to about 100%,
and most preferably from about 90% to about 100%. The heteroatom
sensitive process may be discrete from the countercurrent system, but is
15 preferentially operated in countercurrent mode and may be contained within
the same vessel.

In one embodiment the hydrocarbon feed steam first passes through a co-
current hydrotreating reaction zone which contains one or more
20 hydroprocessing catalyst(s). The effluent may then be passed to at least one
countercurrent reaction zone containing a stacked catalyst/sorbent bed
system.

During normal operation of the system, the heteroatom hydroprocessing
25 catalyst will convert essentially all of the organo heteroatom molecules to the
corresponding hetero-hydride. The hetero-hydride partitions into the vapor
phase due to its inherent vapor pressure under hydroprocessing conditions
and is carried upward by the up flowing hydrogen-containing treat gas. The
sorbent zone sees a negligible amount of heteroatom so that its capacity is
30 not consumed. In the event of a process upset where unreacted organo
heteroatom molecules or the hetero-hydride reaction products break through

the catalyst zone they will be sorbed by the heteroatom sorbent material thereby protecting the downstream heteroatom sensitive process or catalyst.

The sorbent may irreversibly bind with the sorbent which, while protecting the down stream process or catalyst, will result in the sorbent needing to be replaced or regenerated at some frequency. It is preferred that the sorbent material also catalyze or otherwise facilitate the reaction of hydrogen with the sorbed organo heteroatom molecules to form the corresponding hetero-hydride. The hetero-hydride is typically more weakly bound by the sorbent and due to its inherent high vapor pressure can be stripped from the sorbent zone by the up flowing treat gas thereby continuously regenerating the sorbent bed. A third way that the sorbent bed can function is to reversibly bind with the heteroatom and slowly release it to the down stream process or catalyst. This is allowable where the catalyst of downstream process has some tolerance for heteroatom; the tolerance being enhanced if the downstream system is operated in a countercurrent mode of operation. This third type of sorption system may also be enhanced by a small zone of heteroatom hydroprocessing catalyst placed below the sorbent bed and operated in contact with a countercurrent flow of hydrogen containing treat gas. The said additional catalyst zone will convert the organo heteroatom molecules to the corresponding hetero-hydride and allow them to be stripped from the system by the up flowing treat gas.

It is to be understood that all reaction zones and sorption zones can either be in the same vessel separated by non-reaction zones, or any can be in separate vessels. The non-reaction zones in the later case will typically be the transfer lines leading from one vessel to another. It is also possible to mix the sorbent with the catalyst in the bottom of the heteroatom removal zone or the catalyst at the top of the heteroatom sensitive catalyst zone when either or both of these zones are operated with countercurrent hydrogen containing treat gas. This mixing of catalyst and sorbent may be

accomplished by mixing of the two materials prior to formulation into particles or may be accomplished by mixing of the particles after formulation into particles.

- 5 This would allow the construction of smaller volume reactors and/or the production of lower heteroatom streams than possible using conventional co-current flow reactor technology. The said low heteroatom streams can be passed on to other catalysts or processes which are extremely sensitive to poisoning by heteroatoms. This heteroatom sensitivity is sometimes
- 10 sufficiently acute as to prevent the practical use of advanced catalysts. Such catalysts include those which promote ring opening, aromatic saturation, isomerization, and hydrocracking.

If a preprocessing step is performed to remove the so-called "easy

15 heteroatoms", the vapor and liquid are disengaged and the liquid effluent directed to the top of a countercurrent reactor. The vapor from the preprocessing step can be processed separately or combined with the vapor phase product from the countercurrent reactor. The vapor phase product(s) may undergo further vapor phase hydroprocessing if greater reduction in

20 heteroatom and aromatic species is desired or sent directly to a recovery system. The catalyst may be contained in one or more beds in one vessel or multiple vessels. Various hardware (i.e. distributors, baffles, heat transfer devices) may be required inside the vessel(s) to provide proper temperature control and contacting (hydraulic regime) between the liquid, vapors, and

25 catalyst.

Suitable heteroatom hydroprocessing catalyst for use in the upstream countercurrent zone(s) or co-current reaction zone(s) can be any conventional hydroprocessing catalyst and includes hydrotreating catalysts,

30 hydrocracking catalysts, and hydrogenation catalysts; one or more may be used in either zone depending on the starting quality of the feed and the

desired product quality. Most common are those which comprise at least one Group VIII metal, preferably Fe, Co and Ni, more preferably Co and/or Ni, and most preferably Ni; and at least one Group VI metal, preferably Mo and W, on a high surface area support material, which preferably is zeolite or alumina.

Some catalysts which tend to have some heteroatom sensitivity may be used in the lower portion(s) of the countercurrent reaction zone(s) due to the fact that a significant amount of heteroatom will have already been removed by the upstream catalyst and stripped out by up flowing treat gas. Catalysts suitable for said portions are those comprised of a noble or non-noble metal, or metals, of Group VIII of the Periodic Table of the Elements supported in a highly dispersed and essentially uniformly distributed manner on a refractory inorganic support.

Suitable support materials for the catalysts of the present invention include high surface area, refractory materials, such as alumina, silica, aluminosilicates, silicon carbide, amorphous and crystalline silica-aluminas, silica magnesias, boria, titania, zirconia and the like. In one embodiment, the preferred support materials include alumina and the crystalline silica-aluminas, particularly those materials classified as clays or zeolites, more preferably controlled acidity zeolites modified by their manner of synthesis, by the incorporation of acidity moderators, and post-synthesis modifications such as dealumination.

Heteroatom sorbents suitable for use in the practice of the present invention include those selected from several classes of materials known to be reactive toward the organo heteroatom molecules and in some cases the hetero-hydride and capable of binding same in either a reversible or irreversible manner.

One class of materials suitable for such use as heteroatom sorbents are reduced metals which may be employed as bulk materials or supported on an appropriate support material such as an alumina, silica, or a zeolite. Representative metals include those from Groups Ia, Ib, IIa, IIb, IIIA, IVA, VB, VIB, VIIB, VIII or the Periodic Table of the Elements (as displayed inside the front cover of the 64th Edition of the *CRC Handbook of Chemistry and Physics*). Preferred metals include Zn, Fe, Ni, Cu, Mo, Co, Mg, Mn, W, K, Na, Ca, Ba, La, Ce, V, Ta, Nb, Re, Zr, Cr, Ag, Rh, Ir, Pd, Pt, and Sn. These metals may be employed individually or in combination.

Another class of metal based materials suitable for such use as heteroatom sorbents are metal oxides which may be employed as bulk oxides or supported on an appropriate support material such as an alumina, silica, or a zeolite. Representative metal oxides include those of the metals from Groups Ia, Ib, IIa, IIb, IIIA, IVA, VB, VIB, VIIB, VIII or the Periodic Table of the Elements. Preferred metals include Zn, Fe, Ni, Cu, Mo, Co, Mg, Mn, W, K, Na, Ca, Ba, La, Ce, V, Ta, Nb, Re, Zr, Cr, Ag, Rh, Ir, Pd, Pt, and Sn. These metal oxides may be employed individually or in combination.

A third class of metal based materials suitable for such use as heteroatom sorbents are metal sulfides which may be employed as bulk sulfides or supported on an appropriate support material such as an alumina, silica, or a zeolite. Representative metal oxides include those of the metals from Groups Ia, Ib, IIa, IIb, IIIA, IVA, VB, VIB, VIIB, VIII or the Periodic Table of the Elements. Preferred metals include Zn, Fe, Ni, Cu, Mo, Co, Mg, Mn, W, K, Na, Ca, Ba, La, Ce, V, Ta, Nb, Re, Zr, Cr, Ag, Rh, Ir, Pd, Pt, and Sn. These metal sulfides may be employed individually or in combination.

Zeolites and zeolite based materials may serve as heteroatom sorbents for this invention as detailed in US-A-4,831,206 and US-A-4,831,207, both of

which are also incorporated herein by reference. These materials share with spinels the ability to function as regenerable heteroatom sorbents and permit operation of this invention in a mode cycling between heteroatom capture and heteroatom release in either continuous or batch operation depending upon the process configuration. Zeolites incorporating heteroatom active metals by ion exchange are also of value to this invention. Examples include Zn4A, chabazite, and faujasite moderated by the incorporation of zinc phosphate, and transition metal framework substituted zeolites similar to, but not limited to, US-A- 5,185,135 and US-A-5,283,047, both of which are also incorporated herein by reference.

Spinel s represent another class of heteroatom sorbents suitable for use in the practice of the present invention. Such materials are readily synthesized from the appropriate metal salt, frequently a sulfate, and sodium aluminate under the influence of a third agent like sulfuric acid.

Various derivatives of hydrotalcite exhibit high heteroatom capacities and for this reason serve as heteroatom sorbents for this invention. These may include numerous modified and unmodified synthetic and mineral analogs of these as described in US-A-3,539,306; US-A-3,796,792; US-A-3,879,523; and US-A-4,454,244, all of which are also incorporated herein by reference. The high molecular dispersions of the reactive metal make them very effective scavengers for heteroatom bearing molecules.

Also suitable are activated carbons and acidic activated carbons that have undergone treatment, well known to those skilled in the art, to have an enhanced acidic nature. Acidic salts may also be added to the activated carbon, used on other high surface area support or used as bulk sorbents.

The weight ratio of the heteroatom sorbent to the heteroatom removal catalyst may be in the range of from 0.01 to 10, preferably from 0.05 to 5, and more preferably from 0.1 to 1.

- 5 Preferably, the sorbent material also catalyzes or otherwise facilitates the reaction of hydrogen with the sorbed organo heteroatom molecules to form the corresponding hetero-hydride.

10 The countercurrent contacting of an effluent stream from an upstream reaction zone, with hydrogen-containing treat gas, strips dissolved hetero-hydride impurities from the effluent stream, thereby improving both the hydrogen partial pressure and the catalyst performance. That is, the catalyst and sorbent can be on-stream for substantially longer periods of time before regeneration is required. Further, predictable heteroatom removal levels will
15 be achieved by the process of the present invention.

The process of this invention is operable over a range of conditions consistent with the intended objectives in terms of product quality improvement and consistent with any downstream process with which this
20 invention is combined in either a common or sequential reactor assembly. It is understood that hydrogen is an essential component of the process and may be supplied pure or admixed with other passive or inert gases as is frequently the case in a refining or chemical processing environment. It is preferred that the hydrogen stream be heteroatom free, or essentially
25 heteroatom free, and it is understood that the latter condition may be achieved if desired by conventional technologies currently utilized for this purpose.

The various embodiments of the present invention include operating
30 conditions consisting of a temperature in the range of from 100 to 500 °C (212 to 930 °F), preferably from 200 to 450 °C (390 - 840 °F), and more

preferably 225 to 400 °C (437 to 750 °F). Pressures at which the process may operated include those in the range of from 100 to 2000 psig (689 to 13,788 kPa), preferably from 400 to 1200 psig (2758 to 8273 kPa), and more preferably from 450 to 1000 psig (3102 to 6894 kPa). Gas rates at which the process may operated include those in the range of from 100 to 10,000 SCF/B (18 to 1781 m³ gas/m³ oil), preferably from 250 to 7500 SCF/B (45 to 1336 m³ gas/m³ oil), and more preferably from 500 to 5000 SCF/B (89 to 8906 m³ gas/m³ oil). The feed rate velocity at which the process may be operated varies in the range of from 0.1 to 100 LHSV, preferably from 0.3 to 40 LHSV, and more preferably from 0.5 to 30 LHSV.

Quite often the downstream process, catalyst, of product disposition will require that the liquid stream be at a lower temperature than was required in the heteroatom hydroprocessing stream; particularly when the downstream process/catalyst is performing aromatic saturation that is equilibrium limited at higher temperatures. When this is the case it may be desirable to perform the temperature adjustment prior to contacting the liquid stream with the heteroatom sorbent as most of the sorbents having higher sorption capacities at lower temperatures. In such applications, each of the temperature ranges described above may be decreased by as much as 100 °C (180 °F).

The hetero-hydrides formed across the heteroatom hydroprocessing catalyst have a finite solubility in the liquid stream. For this reason it may at time be desirable to include a stripping zone to remove these hetero-hydrides before passing the liquid stream to the sorbent zone. This stripping zone may be contained within the same vessel or a discrete vessel and may include any type of stripper familiar to those skilled in the art.

This invention will allow consistent levels of heteroatom concentration in a liquid effluent stream by utilizing a sorbent bed in countercurrent flow

operation to sorb higher levels of heteroatoms breaking through the heteroatom hydroprocessing zone during process excursions.

- 5 The ranges and limitations provided in the specification and claims are those which are believed to particularly point out and distinctly claim the instant invention. It is, however, understood that other ranges and limitations that perform substantially the same function in substantially the same manner to obtain substantially the same result are intended to be within the scope of the instant invention as defined by the instant specification and the claims.

WHAT IS CLAIMED IS:

1. A process for heteroatom removal from a hydrocarbon stream comprising:

5 (a) feeding said feedstock stream to a first reaction zone comprising a bed of heteroatom hydroprocessing catalyst in contact with a hydrogen-containing treat gas wherein said first reaction zone is operating at conditions effective to remove a first portion of the heteroatom content of said feedstock stream, wherein said first portion removed from said feedstock stream is in the range of 20% to 100%;

10 (b) passing the liquid product stream from (a) to a sorbent zone comprising a bed of heteroatom sorbent material in contact with a hydrogen-containing treat gas wherein said liquid product stream from (a) and said hydrogen-containing treat gas are flowing in a countercurrent direction, wherein said sorbent zone is operating under conditions effective to remove a second portion of the heteroatom from said liquid product stream from (a), wherein said second portion removed from said feedstock stream is in the range of 0% to 80%; and

15 (c) recovering a liquid product stream from (b) wherein the amount of heteroatom remaining is in the range of from 0% to 80%, basis the starting hydrocarbon feedstream which has not be subjected to a heteroatom removal process.

20

2. The process in claim 1 further comprising:

(d) subjecting said liquid product stream from (c) to further heteroatom sensitive processing selected from the group consisting of a process comprising heteroatom sensitive

25

catalyst, a second heteroatom sensitive process not containing a catalyst, a heteroatom sensitive product disposition, and combinations thereof.

- 5 3. The process in claim 1 wherein said reaction zone of (a) is operated with the process stream and the hydrogen containing treat gas flowing countercurrent to one another.
- 10 4. The process in claim 2 wherein said heteroatom sensitive process of (d) comprises at least one reaction zone containing a bed of heteroatom sensitive hydroprocessing catalyst wherein said liquid phase effluent is processed countercurrent to a hydrogen-containing treat gas.
- 15 5. The process in claim 2 wherein said heteroatom sensitive process is at least one reaction zone containing a bed of heteroatom sensitive hydroprocessing catalyst wherein said liquid phase effluent is processed co-current with a hydrogen-containing treat gas.
- 20 6. The process of claim 3 wherein said feed stream is first processed with a hydrogen containing treat gas in at least one co-current reaction zone containing heteroatom hydroprocessing catalyst.
- 25 7. The process of claim 1 wherein said heteroatom sorbent binds the heteroatom with sufficient binding energy so as to be essentially an irreversible sorption.
- 30 8. The process of claim 7 wherein said heteroatom sorbent is a reduced metal or metal oxide as either a bulk material or dispersed on a high surface area support.

- 5
9. The process of claim 1 wherein said heteroatom sorbent also catalyzes the reaction of said organo heteroatom molecules with hydrogen to produce the corresponding hetero-hydride.
10. The process of claim 9 wherein said heteroatom sorbent is a reduced metal, metal oxide, or metal sulfide as either a bulk material or dispersed on a high surface area support, particularly a zeolitic support.
- 10
11. The process of claim 9 wherein the binding energy for said hetero-hydride with said sorbent is less than the binding energy of the organo heteroatom with the sorbent so that said hetero-hydride is desorbed and carried upward by the upward flowing treat gas.
- 15
12. The process of claim 11 wherein said heteroatom sorbent is a reduced metal, metal oxide, or metal sulfide as either a bulk material or dispersed on a high surface area support particularly on a zeolitic support.
- 20
13. The process of claim 12 wherein said metal of the metal, metal oxide, or metal sulfide is a noble metal or combination of noble metals.
- 25
14. The process in claim 1 wherein said heteroatom sorbent binds said heteroatom with sufficiently weak binding energy so as to be essentially a reversible sorption wherein said heteroatom sorbent releases said heteroatom at a rate so as to have a negligible impact on said downstream process.

15. The process of claim 14 wherein said heteroatom sorbent is a zeolite, alumina, clay, acidic salt, spinel, activated carbon, aluminosilicate, hydrotalcite or a combination thereof.
- 5 16. The process in claim 3 wherein said heteroatom sorbent binds said heteroatom with sufficiently weak binding energy so as to be essentially a reversible sorption wherein said heteroatom sorbent releases said heteroatom at a rate so as to have a negligible impact on said downstream process.
- 10 17. The process of claim 1 wherein said hydroprocessing catalyst(s) are selected from the group consisting of hydrotreating catalyst, hydrocracking catalyst, hydrogenation catalyst, hydroisomerization catalyst, ring opening catalyst, catalytic dewaxing catalyst, or a combination thereof.
- 15 18. The process of claim 6 wherein said hydroprocessing catalyst(s) are selected from the group consisting of hydrotreating catalyst, hydrocracking catalyst, hydrogenation catalyst, or a combination thereof.
- 20 19. The process of claim 1 wherein said heteroatom sorbent is selected from the group consisting of reduced metals, metal oxides, metal sulfides, clays, acidic salts, spinels, zeolites, activated carbon, aluminas, aluminosilicates, hydrotalcites or a combination thereof.
- 25 20. The process of claim 19 wherein said heteroatom sorbent reduced metal, metal sulfide or metal oxide is based on a metal selected from the group consisting of Groups Ia, Ib, IIa, IIb, IIIA, IVA, VB, VIB, VIIB, VIII, or a combination thereof of the Periodic Table of the Elements.
- 30

21. The process of claim 1 wherein the temperature of said liquid stream passing between the catalyst zone(s) and sorbent zone(s) is reduced, through injection of quench or heat exchange, so as to improve the sorption capabilities of the sorbent(s).
5
22. The process of claim 1 wherein the said liquid stream passing between the catalyst zone(s) and sorbent zone(s) is passed through a stripping zone(s) to remove the volatile hetero-hydrides before passing into the sorbent zone(s).
10
23. The process of claim 1 wherein said heteroatom sorbent is mixed into said heteroatom hydroprocessing catalyst zone of (a).
- 15 24. The process of claim 4 wherein said heteroatom sorbent is mixed into said downstream catalyst zone (d).
25. The process of claim 2 wherein there is an additional zone of heteroatom hydroprocessing catalyst placed downstream of the heteroatom sorbent bed and operated in contact with a countercurrent flow of a hydrogen containing treat gas prior to said liquid phase effluent being passed to a heteroatom sensitive catalyst, process, or product disposition of (d).
20
- 25 26. The process of claim 14 herein there is an additional zone of heteroatom hydroprocessing catalyst placed downstream of the heteroatom sorbent bed and operated in contact with a countercurrent flow of a hydrogen containing treat gas prior to said liquid phase effluent being passed to a heteroatom sensitive catalyst, process, or product disposition of (d).
30

27. The process of claim 1 wherein said heteroatoms are selected from the group consisting of sulfur, nitrogen, oxygen, the halogens, and mixtures thereof.

5

28. The process of claim 4 wherein the heteroatom sensitive process is an aromatic saturation process.

10

29. The process of claim 3 wherein the heteroatom sensitive process is a selective hydrocracking process.

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C10G 67/06, 65/04	A3	(11) International Publication Number: WO 98/07805 (43) International Publication Date: 26 February 1998 (26.02.98)
(21) International Application Number: PCT/US97/14761 (22) International Filing Date: 22 August 1997 (22.08.97) (30) Priority Data: 60/024,306 23 August 1996 (23.08.96) US (71) Applicant (for all designated States except US): EXXON CHEMICAL PATENTS INC. [US/US]; 5200 Bayway Drive, Baytown, TX 77520-5200 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): IACCINO, Larry L. [-/US]; 2017 San Joaquin Parkway, Friendswood, TX 77546 (US). (74) Agents: RUSSELL, Linda, K.; Exxon Chemical Company, P.O. Box 2149, Baytown, TX 77522-2149 (US) et al.		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims</i> <i>and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 16 April 1998 (16.04.98)
(54) Title: HETEROATOM REMOVAL THROUGH COUNTERCURRENT SORPTION (57) Abstract The present invention relates to a process for heteroatom removal, particularly during process excursions, from petroleum and chemical hydrocarbon streams. The invention is comprised of at least two zones through which the hydrocarbon stream and a hydrogen containing treat gas flow. The first zone contains a bed of heteroatom hydroprocessing catalyst in contact with hydrogen-containing treat gas and the second zone contains heteroatom sorbent material(s) through which the hydrocarbon stream flows countercurrent to the up flowing hydrogen-containing treat gas.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Benin	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/14761

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C10G67/06 C10G65/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 940 330 A (HAROLD BEUTHER ET AL) 24 February 1976 see column 10, line 37 - line 44; claims 1-15	1-29
X	US 3 657 112 A (FRANZ WILLIAM F ET AL) 18 April 1972 see column 2, line 63 - line 65; claims 1-6	1-29

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

18 February 1998

Date of mailing of the international search report

25/02/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Michiels, P

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/14761

Patent document cited in search report	Publication date.	Patent family member(s)	Publication date
US 3940330 A	24-02-76	CA 1029323 A JP 50148409 A	11-04-78 28-11-75
US 3657112 A	18-04-72	NONE	